

# NST10.IP Linear LED outdoor Datasheet



## Product codes

---

Unit:	Series:	Colour temp.:	Beam angle (°):
NST10.IP	LN	3K 4K RGB	DF180

## Electrical

---

<b>Colour temperature:</b> 3000K or 4000K or RGB (Special Order)	<b>Input voltage:</b> 24V	<b>IP rating:</b> IP67	<b>Surge protection:</b> 3100V	<b>Dimmable:</b> Yes
--	------------------------------	---------------------------	-----------------------------------	-------------------------

<b>Driver:</b> BG-030SD-24V (sold separately)	<b>Driver for Pro-LN:</b> Non-Dimmable or Phase or Dali or 010V or SMART (Zigbee 3.0) or CASAMBI	<b>Circuit Wattage:</b> 10W/mWm
---	--	------------------------------------

## Operational

---

<b>Lumen output:</b> 1000lm or 1090lm or N/Alm	<b>Beam angle:</b> DF180°	<b>Operating temp.:</b> -20 to 50°C	<b>Average temp.:</b> 60°C	<b>Lifetime L70, B10:</b> 50,000 hrs (@TA25)
--	------------------------------	--	-------------------------------	---

## Physical

---

<b>Gimbal angle:</b> N/A	<b>Warranty:</b> 7 years	<b>Length:</b> 5.0mm or 1.0mm	<b>Outer Body:</b> White	<b>Version:</b> 1.0
<b>Driver Wattage:</b> 30	<b>Length per Driver:</b> xx			